

TECHNICAL DATA

TYPE	Output power [kW]	Nominal current [A]	Peak current [A]	Mass [kg]	Physical dimensions [mm]				Fastening screws
					Width	Length	Height	Fastening	

THREE PHASE, 3 x 380 to 440VAC INPUT

E3D 0.55	0.55	1.7	2.3	1.5	100	220	107	70 x 210	4 x M4
E3D 0.75	0.75	2.6	4	1.5	100	220	107	70 x 210	4 x M4
E3D 1.1	1.1	3.2	5	2	100	240	144	70 x 230	4 x M4
E3D 1.5	1.5	4.2	6	3	100	240	144	70 x 230	4 x M4
E3D 2.2	2.2	6	9	3	100	240	144	70 x 230	4 x M4
E3D 3	3	8	12	4	100	270	176	70 x 260	4 x M4
E3D 4	4	10	14	4	100	270	176	70 x 260	4 x M4
E3D 5.5	5.5	14	19	6	128	290	220	105 x 280	4 x M5
E3D 7.5	7.5	18	30	8	128	390	220	105 x 380	4 x M5
E3D 11	11	26	37	8	128	390	220	105 x 380	4 x M5

V3D 0.55	0.55	1.7	3	2	128	210	91	90 x 200	4 x M4
V3D 0.75	0.75	2.6	4	2.5	128	210	142	90 x 200	4 x M4
V3D 1.1	1.1	3.2	5	2.5	128	210	142	90 x 200	4 x M4
V3D 1.5	1.5	4.2	6	3	128	240	150	90 x 230	4 x M4
V3D 2.2	2.2	6	9	3	128	240	150	90 x 230	4 x M4
V3D 3	3	8	12	4	128	280	150	90 x 265	4 x M4
V3D 4	4	10	14	4	128	280	150	90 x 265	4 x M4

VLD 4	4	10	15	8	190	290	220	170 x 280	4 x M5
VLD 5.5	5.5	14	19	8	190	290	220	170 x 280	4 x M5
VLD 7.5	7.5	18	30	12	190	390	220	170 x 380	4 x M5
VLD 11	11	26	37	12	190	390	220	170 x 380	4 x M5
VLD 15	15	35	57	14	190	490	220	170 x 470	4 x M5
VLD 22	22	48	75	20	290	490	220	260 x 470	4 x M6

VHD 30	30	62	95	38	300	590	300	260 x 550	4 x M8
VHD 37	37	75	115	38	300	590	300	260 x 550	4 x M8
VHD 45	45	90	135	65	400	740	300	360 x 700	4 x M8
VHD 55	55	110	150	65	400	740	300	360 x 700	4 x M8
VHD 75	75	150	220	80	500	740	300	460 x 700	4 x M8
VHD 90	90	180	255	85	500	790	300	460 x 700	4 x M8
VHD 110	110	220	310	110	500	1100	335	460 x 1040	4 x M10
VHD 132	132	260	360	115	500	1100	335	460 x 1040	4 x M10
VHD 160	160	320	450	120	500	1100	410	460 x 1040	4 x M10
VHD 200	200	400	550	125	500	1100	410	460 x 1040	4db M10

